

## IN THE CLAIMS

Please cancel claims 47-48 without prejudice.

Please amend the following of the claims now pending in the present application, reflecting amendments made previously under Article 34 and shown in the Substitute Specification filed on April 28, 2006, and correcting the numerical order of the claims:

1. (Original) A hand tool comprising:
  - a body,
  - a motor contained within the body,
  - a void space between an internal surface of the body and at least a part of the motor,
  - a fluid inlet port provided in or on the body,
  - a fluid outlet port provided in or on the body, and
  - ducting means which provides a channel for fluid supplied via the fluid inlet port through the void space and then on to the fluid outlet port,
  - said fluid outlet and inlet ports are connectable to fluid supply and fluid extraction conduits respectively,
  - characterised in that a fluid is supplied to said fluid inlet from an external fluid source.

2. (Original) A hand tool as claimed in claim 1 wherein said supply conduit and/or extraction conduit are releasably attachable to said fluid inlet and said fluid outlet respectively.
3. (Currently amended) A hand tool as claimed in claim 1 ~~or claim 2~~ including a fluid transport means capable of providing fluid flow from said external fluid source through said void space via the supply conduit and egressing via the extraction conduit.
4. (Currently amended) A hand tool as claimed in ~~any of the previous claims~~ claim 1 wherein said motor is a brushless DC motor.
5. (Currently amended) A hand tool as claimed in ~~any of the previous claims~~ claim 1 including a controller employed to monitor the temperature of the hand tool or at least one component therein and/or the level of power supply and/or the level of fluid supply to the hand tool.
6. (Original) A hand tool as claimed in claim 5 wherein the controller includes motor diagnostic equipment.

7. (Currently amended) A hand tool as claimed in claim 5 ~~or claim 6~~ wherein said controller is capable of providing a signal to a computer monitoring system to indicate said temperature, level of power supply and/or level of fluid supply.
8. (Original) A hand tool as claimed in claim 7 wherein the computer monitoring system regulates the power supply and/or fluid supply if said controller indicates that the temperature, level of power supply and/or level of fluid supply is outside of predetermined limits.
9. (Currently amended) A hand tool as claimed in ~~any of claims 5-8~~ claim 5 wherein said controller is capable of providing a signal to a visible indicator system to indicate the level of power supply and/or level of fluid supply.
10. (Original) A hand tool as claimed in claim 9 wherein the visible indicator system is capable of indicating if the temperature, level of power supply and/or level of fluid supply is outside of predetermined limits.
11. (Currently amended) A hand tool as claimed in ~~any of claims 5-10~~ claim 5 wherein the controller is mounted remotely to the hand tool.

12. (Currently amended) A hand tool as claimed in ~~any of claims 5–11~~ claim 5, wherein the controller includes an emergency power “off” or power disabling switch.

13. (Currently amended) A hand tool as claimed in ~~any of claims 5–12~~ claim 5, wherein said controller controls energisation of the motor.

14. (Currently amended) A hand tool as claimed in ~~any of the previous claims~~ claim 1, wherein the motor is sealed within a motor housing, the void space existing between the internal surface of the body and at least a part of the motor housing.

15. (Currently amended) A hand tool as claimed in ~~any of the previous claims~~ claim 1, wherein the fluid supplied to the void space provides cooling to the motor.

16. (Currently amended) A hand tool as claimed in ~~any one of the previous claims~~ claim 1, wherein the fluid supplied to the void space is a compressed pneumatic fluid.

17. (Currently amended) A hand tool as claimed in ~~any one of the previous claims~~ claim 1, wherein the fluid supplied to the void space is at a pressure greater than the external environment pressure.

18. (Currently amended) A hand tool as claimed in ~~any the previous claims~~ claim 1, wherein the ducting means causes the fluid supplied to the fluid inlet port to, within the void space, first travel in a direction parallel to the axis of the body and motor housing and then to travel about the axis before again travelling along the axis to the fluid outlet port.

19. (Currently amended) A hand tool as claimed in ~~any one of the previous claims~~ claim 1, wherein the fluid supplied to the void space maintains the motor temperature between about 35°C to about 50°C, and/or maintains the external temperature of the body between about 25°C to about 40°C.

20. (Currently amended) A hand tool as claimed in ~~any one of the previous claims~~ claim 1, wherein the fluid supplied to the void space is provided at between about 15 L/min to about 35L/min, at between about 1.5 Bar to about 3.0 Bar, and at between about 8°C to about 22°C.

21. (Currently amended) A hand tool as claimed in ~~any one of the previous~~  
~~claims~~ claim 1, wherein fluid is supplied to the void space only when the motor is  
operational.

22. (Currently amended) A hand tool as claimed in ~~any one of the previous~~  
~~claims~~ claim 1, wherein the supply conduit also provides electrical power to the  
motor.

23. (Currently amended) A hand tool as claimed in ~~any one of the previous~~  
~~claims~~ claim 1, wherein fluid is supplied to the void space only when the supply  
conduit is connected to the body.

24. (Currently amended) A hand tool as claimed in ~~any of the previous claims~~  
claim 1, wherein said hand tool includes a power output means connected to the  
motor.

25. (Original) A hand tool as claimed in claim 24, wherein the power output  
means is a shaft capable of providing a driving force to a connected implement.

26. (Original) A hand tool as claimed in claim 25, wherein the implement may  
be an implement selected from one of the following types: a rotateable circular  
blade, a reciprocating blade, a pair of connected reciprocating blades, a rotating

drum past a blade, a universal connection means able to attach or fit or house a tool.

27. (Currently amended) A hand tool as claimed in ~~any one of claims 24-26~~ claim 24, wherein the power output means comprises a rotating shaft, a toothed wheel or cog, disc or other suitable gear head.

28. (Currently amended) A hand tool as claimed in ~~any one of claims 24-27~~ claim 24, wherein the power output means includes a gearing system able to translate the power output by the shaft to a pre-determined speed or torque.

29. (Currently amended) A hand tool as claimed in ~~any one of the preceding claims~~ claim 1, wherein said hand tool includes a rotor position sensing means which outputs a signal which enables the position of the motor's rotor to be determined.

30. (Original) A hand tool as claimed in claim 29, wherein the rotor position sensing means comprises a Hall effect sensor.

31. (Currently amended) A hand tool as claimed in claim 29 ~~or claim 30~~, wherein energisation of the motor is determined at least in part on the basis of the rotor position signal.

32. (Currently amended) A hand tool as claimed in ~~any one of claims 5 to 13~~ claim 5, wherein the controller receives manual speed demand input and varies the output speed and/or torque of the motor accordingly.

33. (Currently amended) A hand tool as claimed in ~~any one of the preceding claims~~ claim 1, wherein a power switch handle is used to activate the hand tool.

34. (Original) A hand tool as claimed in claim 33, wherein activation is achieved by pushing a base of a plunger on the handle forward against a biasing force and enabling activation of a sensing switch.

35. (Original) A hand tool as claimed in claim 34, wherein activation of the switch may be via movement of a bevelled surface of the plunger against the switch and then by holding the handle down flush with the hand tool body.

36. (Currently amended) A hand tool as claimed in ~~any of the preceding claims~~ claim 1, wherein a switch is provided for switching electrical supply to the motor on and/or off.

37. (Original) A hand tool as claimed in claim 36, wherein said switch is a non-contact magnetic reed switch located within the body which is sealed.



38. (Currently amended) A hand tool as claimed in ~~any one of the preceding claims~~ claim 1, wherein the hand tool includes a power input means adapted to be supplied with an input DC voltage via a connectable power cable.

39. (Original) A hand tool as claimed in claim 38, wherein the power input means comprises a quick-release plug or socket type arrangement.

40. (Currently amended) A hand tool as claimed in ~~any one of the preceding claims~~ claim 1, wherein the hand tool includes heat dissipation and/or insulation means.

41. (Original) A hand tool as claimed in claim 40, wherein the heat dissipation means are cooling fins.

42. (Currently amended) A hand tool as claimed in claim 40 ~~or claim 41~~, wherein the heat dissipation and/or insulation means substantially surrounds heat generating hand tool components and substantially reduces heat transfer from said hand tool body from transferring heat to an operator.

43. (Currently amended) A hand tool as claimed in ~~any one of the preceding claims~~ claim 1, wherein the hand tool is constructed of metal, plastics or composite

materials.

44. (Currently amended) A hand tool as claimed in ~~any one of the preceding~~ claims claim 1, wherein the body is sealed.

45. (Currently amended) A hand tool as claimed in ~~any one of the preceding~~ claims claim 1, wherein the body is substantially cylindrical in shape and sized to fit into a user's hand.

46. (Currently amended) A hand tool as claimed in ~~any one of the preceding~~ claims claim 1, wherein the motor housing and body are both substantially cylindrical in shape and are aligned coaxially with the void space existing over substantially all of the radially extending region between the motor housing and body.

47-48. (Cancelled)